

Scoring & Timing Solution for Show Jumping



1. Introduction

This is a professional scoring & timing system for Show Jumping match.


System functions include match arrangement, real-time scoring & timing display, players' & referees' info display, rank statistics export & print, slow motion video record & playback, and advertising display can be realized through the coordination of **Match Scoring System, Meet Management System**, etc.

This system is applicable to the competition rules:

--<FEI JUMPING RULES 27th edition>



1.1 System Chart



System Description

- 1) One or two LED displays are set on the site and connected to the control computer.
- 2) Create a local network, connecting the LED screen control PC, referee operation PC, meet management server, results workstation and timing screen to the LAN.
- 3) Place the infrared Photocell and infrared reflector on the site.
- 4) Connect the wireless host to referee operation PC on referee area.



2. Specifications

2.1 Ultra Score Software

| Products | Details |
|--------------------------|--|
| Network standard edition | ◆ Terminal + 1 Display ◆ Supports: Equestrian (Show Jumping) ◆ English version ◆ Including 1 dongle |

Scoreboard display for equestrian






2.2 Wireless Host

| ltem | Details |
|---------------|--|
| <u>.</u> | Model: KS-PTCL-WH Size: 280x200x50 (mm) |
| | Material: Aluminum alloy |
| | Power input: 100~240V AC |
| | Power capacity: 5W |
| Wireless Host | Communication Mode: 433MHz |
| | Wireless communication distance: <=150M (unobstructed) |
| | Supporting item: Show Jumping |
| | Functions: |
| | ◆ Receive wireless signal from photocell |
| | Must be used with Ultra Score software. |



2.3 Timing Handheld


| Item | Details |
|-----------------|---|
| Timing Handheld | Model: KS-PTCL-MT Size: 120x750x20 (mm) Material: PVC Communication mode: wired Length of cable: 3M Supporting competition: Show Jumping Functions: Must be used in conjunction with wireless host. Used for match timing, 45 second countdown, timing to start, pause and reset. Display or hide the timing on the screen. Control the match ringtone. |





2.4 Wireless Photocell

| Item | Details |
|--------------------|---|
| Wireless Photocell | Model: KS-PTCL-PC Size: 184x100x50 (mm) Material: Aluminum alloy Weight: 650G Battery: AA1.5V *2 Power Capacity: 150mW Communication mode: 433MHz wireless Wireless cutting distance<=25M Installation screw hole: 1/4 " Function: ◆ Send an infrared light beam to reflect panel and monitor the light beam for disruptions. ◆ Can be setup as Start, Finish1, or Finish2 easily. |



2.5 Reflect Panel

| Item | Details |
|---------------|--|
| | Model: KS-PTCL-REFL |
| | Size: 92.5x132x55 (mm) |
| | Material: PVC |
| Reflect Panel | Installation screw hole: 1/4 " |
| | Function: |
| | ◆ Must be used in conjunction with wireless photocell to reflect the |
| | light from the photocell. |



2.6 LED Display

| Model: KS-SCRN-LED960160 Size: 960*160*100(mm) Material: Aluminum Input: 12V DC | Item | Details |
|---|-------------|--|
| Function: Must be used together with Show Jumping Scoring Software. Display athlete's number and name. Display athlete's number, current time and penalty. | LED Display | Size: 960*160*100(mm) Material: Aluminum Input: 12V DC Function: ◆ Must be used together with Show Jumping Scoring Software. ◆ Display athlete's number and name. |



2.7 LED Display

| Item | Details |
|-------------|--|
| LED Display | Model: KS-SCRN-LED960480 Size: 1080*600*145(mm) Material: Aluminum |
| | Function: Must be used together with Show Jumping Scoring Software. Display athlete's rank, name and match time. |



2.8 Timing & Penalty Display

| ltem | Details |
|-----------------------------|--|
| Timing & Penalty Display | Model: KS-TRISCRN-LED960320 Shape: Trihedral Size: 960*320(mm) Material: Iron LED Module: Outdoor Bright Full-color Dot Spacing: 10mm Color Gray Scale: 256 Waterproof Grade: IP65 Interface: RS485, wireless 433MHZ Input Voltage: AC160V-AC240V 50HZ Supporting Power Cable: RVV 3*2.5 15m Supporting Data Cable: 10m Function: ◆ Display the countdown before the game, game timing and penalty. |



2.9 Meet Management Server

| Products | Details |
|-----------------|---|
| | Model: KS-MMS-MINI |
| | Size: 260x135x35 (mm) |
| | Weight: 1.0 KG |
| | Input Voltage: 12V DC |
| | RAM: 4GB |
| | CPU: Intel J3160 |
| | Hard Disk: 64G |
| | Communication: LAN*1 |
| | Port: VGA*1, DP*1, USB*2 |
| | Functions: |
| Meet Management | Easy to create an match, and import the match entry information. |
| Server | Arrangement the match with variants of game systems. Including |
| | elimination, round-robin, etc. |
| | Provide the match information to the scoring software on each |
| | venue/court. |
| | Gather the real time score and statistics information from the |
| | scoring software. Monitor the progress of the match. |
| | Generate standard reports for the match, including start-list, |
| | results, combined results, ranking, etc. |
| | Print certifications with adjustable print templates. |
| | Print the team score report. |
| | Open interface with ODF compatible data feed. |



